



**GRAYMONT**

## SAFETY DATA SHEET

**Section 1. Identification of the material and the supplier**

Product: **High Calcium Hydrated Lime**  
 Product Use: Neutralisation, flocculation, stabilisation, absorption.  
 Restriction of Use in NZ: Refer to Section 15

New Zealand Supplier: **Graymont NZ**  
 Address: Hamilton Regional Office  
 214 Collingwood Street, Level 4  
 Hamilton, 3204

Telephone: +64 7 839 3210  
 Toll Free 0800 245 463

**Emergency No: 0800 764 766 (National Poison Centre)**  
**Website: www.graymont.com**

Date of SDS Preparation: 13 August 2025

**Section 2. Hazards Identification**

Classified as hazardous as per EPA Hazardous Substances (Classification) Notice 2020.

**EPA Approval No:**  
**Additives, Process Chemicals, and Raw Materials (Corrosive) – HSR002491**  
**Construction Products (Corrosive) – HSR002542**  
**Fertilisers (Corrosive) – HSR002569**  
**Water Treatment Chemicals (Corrosive) – HSR002681**

**Pictograms**



Signal Word: **DANGER**

GHS Classification and Category	Hazard Code	Hazard Statement
Skin corrosion Cat. 1C	H314	Causes severe skin burns and eye damage.
Serious eye damage Cat. 1	H318	Causes serious eye damage.

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P260	Do not breathe dust, fumes, gas, mist, vapours or spray.
P264	Wash hands thoroughly after handling.
P280	Wear protective clothing as detailed in Section 8.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P310	Immediately call a POISON CENTER or doctor/physician.
P363	Wash contaminated clothing before reuse.

Product Name: **High Calcium Hydrated Lime**  
 Date of SDS: 13 August 2025

SDS Prepared by: Nexreg Compliance Inc.  
 Tel: +1-519-488-5126

P301 + P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304 + P340	IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

<b>Storage Code</b>	<b>Storage Statement</b>
P405	Store locked up.

<b>Disposal Code</b>	<b>Disposal Statement</b>
P501	Dispose of according to Local Regulations or Authorities as per Section 13.

**Section 3. Composition / Information on Hazardous Ingredients**

<b>Ingredients</b>	<b>Wt%</b>	<b>CAS NUMBER.</b>
Calcium Hydroxide	90 - 99	1305-62-0

Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source. However, using the sedimentation method set out in the draft European Standard followed by XRD analysis, all products were shown to have respirable crystalline silica content of <0.1%.

**Section 4. First Aid Measures**

Routes of Exposure:

- If in Eyes                      Get medical attention immediately. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician.
- If on Skin                        Get medical attention immediately. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse
- If Swallowed                    Get medical attention immediately. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- If Inhaled                        Get medical attention immediately. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person

providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

**Most important symptoms and effects, both acute and delayed**

Symptoms:

- Ingestion:** No known significant effects or critical hazards. Over exposure: stomach pains.
- Inhalation:** May cause respiratory irritation. Over exposure: respiratory tract irritation, Coughing.
- Skin:** Causes severe burns. Over exposure: pain or irritation, redness and blistering may occur.
- Eye:** Causes serious eye damage. Over exposure: pain, watering and redness.
- Chronic:** May cause damage to organs through repeated or prolonged exposure. May cause cancer.

**Notes to Doctor:** No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Section 5. Fire Fighting Measures**

<b>Hazard Type</b>	Non Flammable
<b>Hazards from thermal decomposition products</b>	Fumes of Calcium Oxide form when heated to decomposition (540°C).
<b>Suitable Extinguishing media</b>	Use an extinguishing agent suitable for the surrounding fire.
<b>Precautions for firefighters and special protective clothing</b>	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
<b>HAZCHEM CODE</b>	<b>2X</b>

**Section 6. Accidental Release Measures**

**Personal precautions:**

No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

**Environmental precautions:**

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways or air). Water polluting material. May be harmful to the environment if released in large quantities. (pH increase).

**Small Spill:** Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container.

**Large Spill:** Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and

place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container.

## Section 7. Handling and Storage

### Precautions for Handling:

- Read label before use.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Do not breathe dust, fumes, gas, mist, vapours or spray.
- Wash hands thoroughly after handling.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed.
- Remove contaminated clothing and protective equipment before entering eating areas.
- Do not get in eyes or on skin or clothing. Do not ingest.
- Avoid release to the environment.
- If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator.
- Wear protective clothing as detailed in Section 8.
- Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use.
- Empty containers retain product residue and can be hazardous.
- Do not reuse container.

### Precautions for Storage:

- Keep out of reach of children.
- Store locked up.
- Store in original container protected from direct sunlight in a dry, cool and well ventilated area, away from incompatible materials (see Section 10) and food and drink.
- Store to minimise dust generation.
- Keep container tightly closed and sealed until ready for use.
- Containers that have been opened must be carefully resealed and kept upright to prevent leakage.
- Do not store in unlabelled containers.
- Use appropriate containment to avoid environmental contamination.

## Section 8 Exposure Controls / Personal Protection

### WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance		TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Calcium hydroxide	[1305-62-0]	-	5	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13<sup>TH</sup> EDITION.

### Engineering Controls

If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## Personal Protection Equipment



<b>Eyes</b>	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
<b>Hands</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
<b>Skin</b>	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
<b>Respiratory</b>	Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Wear an appropriate NIOSH approved respirator if concentration levels exceed the safe exposure limits.
<b>General</b>	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 9 Physical and Chemical Properties

<b>Appearance</b>	Solid (fine powder)
<b>Colour</b>	White
<b>Odour</b>	Sweet, soil like odour
<b>Odour Threshold</b>	Not available
<b>pH</b>	12.45 [Sat. Soln] @ 25°C
<b>Boiling Point</b>	2850°C
<b>Melting Point</b>	2570 to 2625°C
<b>Freezing Point</b>	Not available
<b>Flash Point</b>	Not available
<b>Flammability</b>	Not Flammable
<b>Upper and Lower Explosive Limits</b>	Not available
<b>Vapour Pressure</b>	Not available
<b>Vapour Density</b>	Not available
<b>Relative Density</b>	2.3 to 2.4
<b>Water Solubility</b>	0.165g/100g at 20°C
<b>Partition Coefficient:</b>	Not available
<b>Auto-ignition Temperature</b>	Not available
<b>Decomposition Temperature</b>	540°C
<b>Kinematic Viscosity</b>	Not available

### Section 10. Stability and Reactivity

<b>Stability of Substance</b>	The product is stable.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to Avoid</b>	Do not allow hydrated lime to come into contact with incompatible materials. e.g. acids, reactive fluoridated compounds, reactive brominated compounds. reactive powdered metals, organic acid anhydrides, nitro-organic compounds, reactive phosphorous compounds, interhalogenated compounds.
<b>Incompatible Materials</b>	Reactive or incompatible with the following materials: oxidising materials and acids.
<b>Hazardous Decomposition Products</b>	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### Section 11 Toxicological Information

#### Acute Effects:

<b>Swallowed</b>	Not applicable however over exposure could cause stomach pains. Repeated exposure may cause severe mucous membrane irritation, bronchitis and pneumonia.
<b>Dermal</b>	Not applicable.
<b>Inhalation</b>	Not applicable may include respiratory tract irritation and coughing.
<b>Eye</b>	Causes serious eye damage. Symptoms may include pain, watering and redness.
<b>Skin</b>	Causes severe burns. Symptoms include pain or irritation, redness and blistering may occur. Prolonged exposure may cause irritant dermatitis.

#### Chronic Effects:

<b>Carcinogenicity</b>	Not applicable.
<b>Reproductive Toxicity</b>	Not applicable.
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	Not applicable.
<b>STOT/SE</b>	Not applicable.
<b>STOT/RE</b>	Not applicable.

#### Acute toxicity for components.

#### Calcium Hydroxide :

LC50 oral mouse = 7340 mg/kg (rat)

### Section 12. Ecotoxicological Information

This material is harmful to aquatic life.

<b>Persistence and degradability</b>	No data available
<b>Bioaccumulation</b>	No data available
<b>Mobility in Soil</b>	No data available
<b>Other adverse effects</b>	No data available

Product/ingredient	Result	Species	Exposure
--------------------	--------	---------	----------

Calcium Hydroxide	Acute LC50 33884.4 µg/L Fresh water	Fish - Clarias gariepinus - Fingerling	96 hours
-------------------	-------------------------------------	--	----------

### Section 13. Disposal Considerations

#### Disposal Method:

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues.

**Precautions or methods to avoid:** Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### Section 14 Transport Information

**This product is NOT classified as a Dangerous Good for transport in NZ; NZS 5433:2020**

### Section 15 Regulatory Information

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Codes:

**Additives, Process Chemicals, and Raw Materials (Corrosive) – HSR002491**

**Construction Products (Corrosive) – HSR002542**

**Fertilisers (Corrosive) – HSR002569**

**Water Treatment Chemicals (Corrosive) – HSR002681**

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	Not required
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000kg
Emergency Response Plan	10 000kg
Secondary Containment	10 000kg
Restriction of Use	Only use for the intended purpose. Not for use as a pesticide or veterinary medicine.

### Section 16 Other Information

#### Glossary

Cat	Category
EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.

Product Name: **High Calcium Hydrated Lime**

SDS Prepared by: Nexreg Compliance Inc.

Date of SDS: 13 August 2025

Tel: +1-519-488-5126

TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

**Disclaimer**

This document was created by a 3rd party service that has advertised to Nexreg Compliance, Inc. (Nexreg) specialized regulatory knowledge and capabilities in the region(s) where this document is stated to be compliant. We believe the statements, technical information, translations and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. In the event that there is a dispute regarding the document's compliance or content Nexreg will endeavour to provide all reasonable assistance to remedy the problem. It is ultimately the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use. The information herein is given in good faith, but no warranty, express or implied is made.

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the New Zealand distributor, if further information is required.

Issue Date: 13 August 2025                      Review Date: 13 August 2030