



Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 2022-12-16 Revision date: 2025-05-07 Supersedes: 2025-03-13 Version: 2.2

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Dolomitic Limestone

1.2. Other means of identification

Product type : Solid
Other means of identification : Dolostone, Dolomite, Dolomitic Limestone.

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Desulphurisation, Neutralisation, Aggregates, Mineral filler and pigment, Flux agent, Liming material
Restrictions on use : None known

1.4. Supplier's details

Manufacturer

GRAYMONT
#200-10991 Shellbridge Way
Richmond, BC, V6X 3C6 - Canada
T 1 604 207-4292; Toll free 1 866 207-4292 - F 1 604 207-9014
www.graymont.com

Distributor

GRAYMONT
585 W Southridge Way
Sandy, Utah, 84070 - United States
T +1 801-262-3942

1.5. Emergency phone number

Emergency number : CHEMTREC 1 (800) 424-9300
CHEMTREC International +1 (703) 527-3887 24 hr

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Carcinogenicity, Category 1A
Specific target organ toxicity, Repeated exposure, Category 1

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) : Danger
Hazard statements (GHS) : May cause cancer (Inhalation).
Causes damage to organs (lungs) through prolonged or repeated exposure
Precautionary statements (GHS) : Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves, protective clothing, eye protection and face protection.
If exposed or concerned: Get medical advice/attention.

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%Weight
Calcium carbonate	Calcium carbonate C.I. Pigment White 18 / Calcium carbonate / Pigment White 18 / C.I. 77220 / Carbonic acid, calcium salt / CALCIUM CARBONATE / CI 77220 / calcium carbonate	CAS-No.: 471-34-1	50 – 75
Carbonic acid, magnesium salt (1:1)	Carbonic acid, magnesium salt (1:1) MAGNESIUM CARBONATE / magnesite / Magnesite / CI 77713 / Carbonate, magnesium / C.I. 77713 / Magnesium carbonate	CAS-No.: 546-93-0	50 – 75
Quartz	Quartz Quartz (SiO2) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz / Silica, crystalline, .alpha.-quartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline-.alpha.quartz / Silica, .alpha.-quartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	CAS-No.: 14808-60-7	0.1 – 1

Comments : Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source.
Any concentration shown as a range is to protect confidentiality or is due to batch variation. If a generic chemical name is shown and/or the CAS number is not disclosed, the specific chemical identity has been withheld as a trade secret.

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Metal oxides.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

For non-emergency personnel

No additional information available

For emergency responders

Environmental precautions	: Prevent entry to sewers and public waters.
---------------------------	--

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

6.2. Methods and materials for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Minimise dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Provide ventilation.
- For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Avoid generating dust. Use only outdoors or in a well-ventilated area. Good housekeeping is important to prevent accumulation of dust. Ensure adequate natural or mechanical ventilation in the form local or general exhaust ventilation is in use to ensure exposure is below established regulatory limits. If ventilation is not adequate, use respiratory protection in the form of a CSA/NIOSH- Approved Particulate Filtering Facepiece Respirators such as an N95 respirator or equivalent.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Store in dust-tight, dry, labelled containers. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Calcium carbonate (471-34-1)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (Limestone)
OEL STEL	20 mg/m ³ (Limestone)
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (Limestone)
OEL STEL	20 mg/m ³ (Limestone)
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWAEV)	10 mg/m ³ (total dust)
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (Limestone)
OEL STEL	20 mg/m ³ (Limestone)
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	30 mppcf 10 mg/m ³
OEL STEL	20 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Carbonic acid, magnesium salt (1:1) (546-93-0)	
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (total dust (Magnesite)) 3 mg/m ³ (respirable fraction (Magnesite))
Canada (Northwest Territories) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (Magnesite)
OEL STEL	20 mg/m ³ (Magnesite)
Canada (Nunavut) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (Magnesite)
OEL STEL	20 mg/m ³ (Magnesite)
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWAEV)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust (Magnesite))
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
OEL STEL	20 mg/m ³

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Carbonic acid, magnesium salt (1:1) (546-93-0)	
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	10 mg/m ³ (total dust (Magnesite)) 5 mg/m ³ (respirable dust (Magnesite))
Quartz (14808-60-7)	
Canada (Alberta) - Occupational Exposure Limits	
Local name	Silica-Crystalline: Quartz
OEL TWA	0.025 mg/m ³ (respirable particulate)
Notations and remarks	Carcinogenicity A2
Regulatory reference	Alberta Regulation 191/2021
Canada (British Columbia) - Occupational Exposure Limits	
Local name	Silica, Crystalline - alpha quartz
OEL TWA	0.025 mg/m ³ (respirable)
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Manitoba) - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2023
Canada (New Brunswick) - Occupational Exposure Limits	
OEL TWA	0.025 mg/m ³ (respirable fraction)
Canada (Newfoundland and Labrador) - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2023
Canada (Northwest Territories) - Occupational Exposure Limits	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline))
Notations and remarks	Designated substance
Regulatory reference	Occupation Health and Safety Regulations R-039-2015 (R-013-2020)
Canada (Nova Scotia) - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2023

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Quartz (14808-60-7)	
Canada (Nunavut) - Occupational Exposure Limits	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline))
Notations and remarks	Designated substance
Regulatory reference	Occupational Health and Safety Regulations, Nu Reg 003-2016 (Amendment R-044-2021)
Canada (Prince Edward Island) - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Notations and remarks	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
Regulatory reference	ACGIH 2023
Canada (Ontario) - Occupational Exposure Limits	
Local name	Silica, Crystalline - Quartz
OEL TWA EV	0.1 mg/m ³ (designated substances regulation-respirable fraction (Silica, crystalline))
Regulatory reference	Ontario Occupational Exposure Limits under Regulation 833
Canada (Quebec) - Occupational Exposure Limits	
Local name	Silica - Crystalline, Quartz
VEMP (OEL TWA EV)	0.1 mg/m ³ (respirable dust)
Notations and remarks	C2, EM
Regulatory reference	S-2.1, r. 13 - Regulation respecting occupational health and safety
Canada (Saskatchewan) - Occupational Exposure Limits	
Local name	Silica - Crystalline: Quartz
OEL TWA	0.05 mg/m ³ (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)))
Notations and remarks	Designated Chemical Substance
Regulatory reference	The Occupational Health and Safety Regulations, 2020. Chapter S-15.1 Reg 10
Canada (Yukon) - Occupational Exposure Limits	
OEL TWA	300 particle/mL (Silica - Quartz, crystalline)
USA - ACGIH - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
ACGIH chemical category	Suspected Human Carcinogen
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Total Dust) (Silica: Crystalline)
OSHA PEL TWA	50 µg/m ³ (Respirable crystalline silica)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m ³ / (%SiO ₂ +2)) for mg/m ³ . CAS No. source: eCFR Table Z-1.

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Quartz (14808-60-7)	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - IDLH - Occupational Exposure Limits	
IDLH	50 mg/m ³ (respirable dust)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL TWA	0.05 mg/m ³ (respirable dust)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Safety glasses or goggles are recommended when using product.
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Colour	: White to grey
Odour	: Odourless
Odour threshold	: No data available
pH	: 9 – 9.2 at 25 °C (77 °F)
Melting point	: Not applicable
Freezing point	: Not applicable
Boiling point	: Not applicable
Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: Not applicable
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: Not applicable
Relative vapour density at 20°C/ 68 °F	: Not applicable
Relative density	: 2.75 – 2.99
Solubility	: Water: 0.03 % at 20 °C (68 °F)
Partition coefficient n-octanol/water	: Not applicable
Auto-ignition temperature	: Not applicable

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Decomposition temperature	: 725 °C (1337 °F)
Viscosity, kinematic	: Not applicable
Explosive limits	: Not applicable
Particle characteristics	: No data available

Calcium carbonate

Boiling point	(decomposes)
---------------	--------------

Carbonic acid, magnesium salt (1:1)

Boiling point	900 °C
---------------	--------

Quartz

Boiling point	2230 °C
---------------	---------

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Incompatible materials.

10.5. Incompatible materials

Oxidizing materials. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Calcium carbonate (471-34-1)

LD50 oral rat	6450 mg/kg (Source: NLM_CIP)
LD50 dermal rat	> 2000 mg/kg (Source: ECHA_API)

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Calcium carbonate (471-34-1)	
LC50 inhalation rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Carbonic acid, magnesium salt (1:1) (546-93-0)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
Skin corrosion/irritation	: Not classified. pH: 9 – 9.2 at 25 °C (77 °F)
Calcium carbonate (471-34-1)	
pH	8 – 9 (aqueous solution)
Serious eye damage/irritation	: Not classified. pH: 9 – 9.2 at 25 °C (77 °F)
Calcium carbonate (471-34-1)	
pH	8 – 9 (aqueous solution)
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: May cause cancer (Inhalation). Risk of cancer depends on duration and level of exposure.
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Causes damage to organs (lungs) through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
Calcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Quartz (14808-60-7)	
Additional information	Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a scarring of the lungs. This disease may be disabling as it reduces lung capacity. The risk of contracting silicosis and the severity of the disease is related to the amount of dust exposure and the length of time (usually years) of exposure.

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified.
Dolomitic Limestone	
Viscosity, kinematic	Not applicable
Calcium carbonate (471-34-1)	
Viscosity, kinematic	No data available
Carbonic acid, magnesium salt (1:1) (546-93-0)	
Viscosity, kinematic	No data available
Quartz (14808-60-7)	
Viscosity, kinematic	No data available
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: No known significant effects or critical hazards.
Hazardous to the aquatic environment, short-term (acute)	: Not classified.
Hazardous to the aquatic environment, long-term (chronic)	: Not classified.

Calcium carbonate (471-34-1)	
EC50 72h - Algae [1]	> 14 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i>)
Carbonic acid, magnesium salt (1:1) (546-93-0)	
EC50 72h - Algae [1]	> 18.5 mg/l Test organisms (species): <i>Desmodesmus subspicatus</i> (previous name: <i>Scenedesmus subspicatus</i>)

12.2. Persistence and degradability

Dolomitic Limestone	
Persistence and degradability	Not established.
Calcium carbonate (471-34-1)	
Persistence and degradability	Rapidly degradable
Carbonic acid, magnesium salt (1:1) (546-93-0)	
Persistence and degradability	Rapidly degradable

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Quartz (14808-60-7)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Dolomitic Limestone	
Partition coefficient n-octanol/water	Not applicable
Bioaccumulative potential	Not established.

Calcium carbonate (471-34-1)	
BCF - Fish [1]	(no bioaccumulation)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone	: Not classified.
Fluorinated greenhouse gases	: No
Other information	: No other effects known.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations	: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
--	---

SECTION 14 Transport information

In accordance with DOT / TDG / IMDG / IATA

14.1. UN Number

Not regulated for transport

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT)	: Not regulated
Proper Shipping Name (TDG)	: Not regulated
Proper Shipping Name (IMDG)	: Not regulated
Proper Shipping Name (IATA)	: Not regulated

14.3. Transport hazard class(es)

DOT	
Transport hazard class(es) (DOT)	: Not regulated

TDG	
Transport hazard class(es) (TDG)	: Not regulated

IMDG	
Transport hazard class(es) (IMDG)	: Not regulated

IATA	
Transport hazard class(es) (IATA)	: Not regulated

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

14.4. Packing group

Packing group (DOT)	: Not regulated
Packing group (TDG)	: Not regulated
Packing group (IMDG)	: Not regulated
Packing group (IATA)	: Not regulated

14.5. Environmental hazards

Other information	: No supplementary information available.
-------------------	---

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IMDG
Not regulated

IATA
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

15.3. State regulations

 **WARNING:** This product can expose you to Silica, respirable crystalline, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Carbonic acid, magnesium salt (1:1)(546-93-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Massachusetts - Right To Know List
Quartz(14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List

Dolomitic Limestone

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 05/07/2025

Issue date : 12/16/2022

Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com

 NEXREG

Indication of changes:		
Section	Changed item	Comments
1	Supplier information	Modified V2.2

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.