



# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Issue date: 2022-10-18  
Revision date: 2022-10-18  
Version: 1.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Colored Mortar Mix  
Product code : Not available  
Product type : Solid  
Other means of identification : Not available

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Masonry construction.

#### 1.3. Supplier

##### Manufacturer

GRAYMONT  
#200-10991 Shellbridge Way  
Richmond, BC V6X 3C6 - Canada  
T 1 604 207-4292 - F 1 604 207-9014

##### Distributor

Graymont Western US Inc  
585 W Southridge Way  
Sandy, Utah 84070 - United States  
T +1 801-262-3942

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC, US (800-424-9300), INTERNATIONAL: (703-527-3887)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Skin corrosion/irritation, Category 2  
Serious eye damage/eye irritation, Category 1  
Skin sensitisation, Category 1  
Carcinogenicity Category 1A  
Specific target organ toxicity – Single exposure, Category 3  
Specific target organ toxicity – Repeated exposure, Category 1

#### 2.2. GHS Label elements, including precautionary statements

##### GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause cancer (Inhalation).  
Causes damage to organs (lungs) through prolonged or repeated exposure.

Precautionary statements (GHS) :

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Do not breathe dust/fume/gas/mist/vapours/spray.  
Wash hands, forearms and face thoroughly after handling.  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves/protective clothing/eye protection/face protection.  
If exposed or concerned: Get medical advice/attention.  
If on skin: Wash with plenty of water.  
Take off contaminated clothing and wash it before reuse.  
If skin irritation or rash occurs: Get medical advice/attention.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Call a poison center or doctor if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a poison center or doctor.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Cement, portland, chemicals	Cement, portland, chemicals Portland cement / Silicate, portland cement / Cement (Portland) / Cement kiln dust / Cement Portland	CAS-No.: 65997-15-1	40 – 70
Calcium hydroxide	Calcium hydroxide Calcium dihydroxide / Calcium hydroxide (Ca(OH) <sub>2</sub> ) / Hydrated lime / Lime, hydrated / CALCIUM HYDROXIDE / Slaked lime	CAS-No.: 1305-62-0	10 – 50
Diiron trioxide	Diiron trioxide C.I. 77491 / C.I. Pigment Red 101 / Diiron trioxide / Ferric oxide / Iron sesquioxide / Iron(III) oxide / Red Iron Oxide / Rouge / CI 77491 / Iron trioxide / Sienna / Pigment Red 101 / Red iron oxide / Red iron oxide pigment / Iron Oxide Red / Diiron(III) trioxide / Iron oxide / Ferric oxide red / Iron oxide, red	CAS-No.: 1309-37-1	25 – 50
Magnesium oxide (MgO)	Magnesium oxide (MgO) Calcined magnesite / Magnesium oxide / MAGNESIUM OXIDE / Magnesia	CAS-No.: 1309-48-4	25 – 50

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Name	Chemical name / Synonyms	Product identifier	%
Calcium sulfate	Calcium sulfate Calcium sulfate / Calcium sulphate / CALCIUM SULFATE / Calcium sulfate, anhydrous / C.I. 77231 / Calcium sulfate dihydrate / CI 77231 / calcium sulfate anhydrous	CAS-No.: 7778-18-9	10 – 25
Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O)	Gypsum (Ca(SO <sub>4</sub> ).2H <sub>2</sub> O) Gypsum	CAS-No.: 13397-24-5	10 – 25
Calcium oxide	Calcium oxide Lime / Quicklime / CALCIUM OXIDE / Quicklime (CaO) / Calcium oxide (CaO) / Lime (calcium oxide)	CAS-No.: 1305-78-8	0.1 – 10
Quartz	Quartz Quartz (SiO <sub>2</sub> ) / Silica, crystalline, quartz / Crystalline silica, quartz / .alpha.-Quartz / Silica, crystalline, .alpha.-quartz / QUARTZ / Crystalline silica in the form of quartz / Quartz, silica / Quartz (respirable fraction) / Silica dust / Silica, crystalline-.alpha.quartz / Silica, .alpha.-quartz / Silicon dioxide / Silica, quartz / Silica, crystalline / Quartz (crystalline silica) / Silica dust, crystalline / QUARTZ POWDER / Silica, crystalline (quartz)	CAS-No.: 14808-60-7	0.0001 – 1

Comments : Crystalline silica has been found in some products at or above detection level 0.1%. Concentration is dependent upon limestone source.  
Any concentration shown as a range is to protect confidentiality or is due to batch variation. If a generic chemical name is shown and/or the CAS number is not disclosed, the specific chemical identity has been withheld as a trade secret.

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
First-aid measures after skin contact : If skin irritation occurs: Wash skin with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.  
First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.  
Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.  
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
Chronic symptoms : May cause cancer. Causes damage to organs through prolonged or repeated exposure.

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### 4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.  
Unsuitable extinguishing media : Do not use water jet.

### 5.2. Specific hazards arising from the chemical

Fire hazard : None.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

#### 6.1.1. For non-emergency personnel

No additional information available

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).  
Methods for cleaning up : Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. . Provide ventilation. Avoid dust formation.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Do not breathe dust. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Avoid generating dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended. Good housekeeping is important to prevent accumulation of dust. Wear appropriate PPE (see Section 8).

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store locked up. Store in a well-ventilated place. Store in dust-tight, dry, labelled containers. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Colored Mortar Mix	
No additional information available	
Cement, portland, chemicals (65997-15-1)	
Canada (Alberta) - Occupational Exposure Limits	
OEL TWA	10 mg/m <sup>3</sup>
Regulatory reference	Alberta Regulation 87/2009 (Alberta Regulation 182/2019)
Canada (Quebec) - Occupational Exposure Limits	
VEMP (OEL TWA)	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-total dust) 5 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-respirable dust)
Canada (British Columbia) - Occupational Exposure Limits	
OEL TWA	1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate)
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
Canada (Ontario) - Occupational Exposure Limits	
OEL TWA	1 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate matter)
Canada (Saskatchewan) - Occupational Exposure Limits	
OEL TWA	10 mg/m <sup>3</sup>
OEL STEL	20 mg/m <sup>3</sup>
USA - ACGIH - Occupational Exposure Limits	
Local name	Portland cement
ACGIH OEL TWA	1 mg/m <sup>3</sup> (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm func; resp symptoms; asthma. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA [1]	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Cement, portland, chemicals (65997-15-1)</b>	
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	5000 mg/m <sup>3</sup>
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>USA - MSHA - Occupational Exposure Limits</b>	
MSHA PEL TWA 8/40 h	1 mg/m <sup>3</sup> (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
<b>Calcium hydroxide (1305-62-0)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup>
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWA)	5 mg/m <sup>3</sup>
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup>
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup>
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup>
OEL STEL	10 mg/m <sup>3</sup>
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	5 mg/m <sup>3</sup>
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA [1]	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	5 mg/m <sup>3</sup>
<b>USA - MSHA - Occupational Exposure Limits</b>	
MSHA PEL TWA 8/40 h	5 mg/m <sup>3</sup>
<b>Diiron trioxide (1309-37-1)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup> (respirable)
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWA)	5 mg/m <sup>3</sup> (dust and fume)
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (regulated under Rouge-total particulate (Rouge)) 3 mg/m <sup>3</sup> (regulated under Rouge: particulate matter containing no Asbestos and <1% Crystalline silica-respirable particulate (Rouge)) 5 mg/m <sup>3</sup> (dust and fume)
OEL STEL	10 mg/m <sup>3</sup> (fume)

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Diiron trioxide (1309-37-1)</b>	
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup> (respirable particulate matter)
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup> (dust and fume) 10 mg/m <sup>3</sup> (regulated under Rouge)
OEL STEL	10 mg/m <sup>3</sup> (dust and fume) 20 mg/m <sup>3</sup> (regulated under Rouge)
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	5 mg/m <sup>3</sup> (respirable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Iron oxide fume
OSHA PEL TWA [1]	10 mg/m <sup>3</sup> (fume) 15 mg/m <sup>3</sup> (total dust (Rouge)) 5 mg/m <sup>3</sup> (respirable fraction (Rouge))
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	2500 mg/m <sup>3</sup> (dust and fume)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	5 mg/m <sup>3</sup> (dust and fume)
<b>USA - MSHA - Occupational Exposure Limits</b>	
MSHA PEL TWA 8/40 h	5 mg/m <sup>3</sup> (respirable particulate matter)
<b>Magnesium oxide (MgO) (1309-48-4)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (fume)
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWA)	10 mg/m <sup>3</sup> (inhalable dust)
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (fume, inhalable) 3 mg/m <sup>3</sup> (respirable dust and fume)
OEL STEL	10 mg/m <sup>3</sup> (respirable dust and fume)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (inhalable fraction)
OEL STEL	20 mg/m <sup>3</sup> (inhalable fraction)
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	10 mg/m <sup>3</sup> (inhalable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Magnesium oxide (MgO) (1309-48-4)</b>	
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA [1]	15 mg/m <sup>3</sup> (fume, total particulate)
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	750 mg/m <sup>3</sup> (fume)
<b>USA - MSHA - Occupational Exposure Limits</b>	
MSHA PEL TWA 8/40 h	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Calcium sulfate (7778-18-9)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup>
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWA)	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-inhalable dust)
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (inhalable)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (Gypsum and Plaster of Paris)
OEL STEL	20 mg/m <sup>3</sup> (Gypsum and Plaster of Paris)
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA [1]	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>USA - MSHA - Occupational Exposure Limits</b>	
MSHA PEL TWA 8/40 h	10 mg/m <sup>3</sup> (inhalable particulate matter)
<b>Gypsum (Ca(SO<sub>4</sub>).2H<sub>2</sub>O) (13397-24-5)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (Calcium sulphate)
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWA)	10 mg/m <sup>3</sup> (containing no Asbestos and <1% Crystalline silica-inhalable dust (Calcium sulfate)
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (total dust) 3 mg/m <sup>3</sup> (respirable fraction) 10 mg/m <sup>3</sup> (regulated under Calcium sulfate-inhalable)
OEL STEL	20 mg/m <sup>3</sup> (total)



# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Gypsum (Ca(SO<sub>4</sub>).2H<sub>2</sub>O) (13397-24-5)</b>	
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate))
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup>
OEL STEL	20 mg/m <sup>3</sup>
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate))
<b>USA - OSHA - Occupational Exposure Limits</b>	
OSHA PEL TWA [1]	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
<b>USA - MSHA - Occupational Exposure Limits</b>	
MSHA PEL TWA 8/40 h	10 mg/m <sup>3</sup> (inhalable particulate matter (Calcium sulfate))
<b>Calcium oxide (1305-78-8)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
OEL TWA	2 mg/m <sup>3</sup>
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWA)	2 mg/m <sup>3</sup>
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
OEL TWA	2 mg/m <sup>3</sup>
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWA	2 mg/m <sup>3</sup>
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	2 mg/m <sup>3</sup>
OEL STEL	4 mg/m <sup>3</sup>
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Calcium oxide
ACGIH OEL TWA	2 mg/m <sup>3</sup>
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2020
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Calcium oxide
OSHA PEL TWA [1]	5 mg/m <sup>3</sup>
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	25 mg/m <sup>3</sup>

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Calcium oxide (1305-78-8)</b>	
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	2 mg/m <sup>3</sup>
<b>USA - MSHA - Occupational Exposure Limits</b>	
MSHA PEL TWA 8/40 h	2 mg/m <sup>3</sup>
<b>Quartz (14808-60-7)</b>	
<b>Canada (Alberta) - Occupational Exposure Limits</b>	
Local name	Silica-Crystalline: Quartz
OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate)
Notations and remarks	Carcinogenicity A2
Regulatory reference	Alberta Regulation 191/2021
<b>Canada (Quebec) - Occupational Exposure Limits</b>	
VEMP (OEL TWA)	0.1 mg/m <sup>3</sup> (respirable dust)
<b>Canada (British Columbia) - Occupational Exposure Limits</b>	
Local name	Silica, Crystalline - alpha quartz
OEL TWA	0.025 mg/m <sup>3</sup> (respirable)
Notations and remarks	ACGIH Carcinogenicity category A2; IARC group 1 carcinogen
Regulatory reference	OHS Guidelines Part 5: Chemical Agents and Biological Agents (WorkSafe BC)
<b>Canada (Ontario) - Occupational Exposure Limits</b>	
OEL TWA	0.1 mg/m <sup>3</sup> (designated substances regulation-respirable fraction (Silica, crystalline))
<b>Canada (Saskatchewan) - Occupational Exposure Limits</b>	
OEL TWA	0.05 mg/m <sup>3</sup> (Trydimite removed-respirable fraction (Silica - crystalline (Trydimite removed)))
<b>USA - ACGIH - Occupational Exposure Limits</b>	
Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 mg/m <sup>3</sup> (respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
ACGIH chemical category	Suspected Human Carcinogen
Regulatory reference	ACGIH 2022
<b>USA - OSHA - Occupational Exposure Limits</b>	
Local name	Quartz (Total Dust) (Silica: Crystalline)
OSHA PEL TWA [1]	50 µg/m <sup>3</sup> (Respirable crystalline silica)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m <sup>3</sup> / (%SiO <sub>2</sub> +2)) for mg/m <sup>3</sup> . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
<b>USA - IDLH - Occupational Exposure Limits</b>	
IDLH	50 mg/m <sup>3</sup> (respirable dust)
<b>USA - NIOSH - Occupational Exposure Limits</b>	
NIOSH REL TWA	0.05 mg/m <sup>3</sup> (respirable dust)

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

### Quartz (14808-60-7)

#### USA - MSHA - Occupational Exposure Limits

MSHA PEL TWA 8/40 h	30 mg/m <sup>3</sup> / (%SiO <sub>2</sub> ) + 2 mg/m <sup>3</sup> (Total dust) 10 mg/m <sup>3</sup> / (%SiO <sub>2</sub> ) + 2 mg/m <sup>3</sup> (Respirable dust)
---------------------	---

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Wear suitable gloves resistant to chemical penetration

#### Eye protection:

Wear eye/face protection

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: Various colours
Odour	: Earthy
Odour threshold	: No data available
pH	: 12 – 13 at 25°C / 77 °F
Melting point	: ≈ 2580 °C (4676 °F)
Freezing point	: No data available
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: Not applicable
Flammability	: Not applicable
Vapour pressure	: Not applicable
Relative vapour density at 20 °C / 68 F°	: Not applicable
Relative density	: 2.6 – 3.2
Density	: 2.6 – 3.2 g/cm <sup>3</sup>
Solubility	: No data available
Partition coefficient n-octanol/water	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive limits	: Not applicable

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Explosive properties : No data available  
Oxidising properties : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No specific test data related to reactivity available for this product or its ingredients.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Incompatible materials.

### 10.5. Incompatible materials

Acids. Reactive materials.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.  
Acute toxicity (dermal) : Not classified.  
Acute toxicity (inhalation) : Not classified.

Calcium hydroxide (1305-62-0)	
LD50 oral rat	7340 mg/kg
LD50 dermal rat	> 2500 mg/kg
LC50 inhalation rat	> 6.04 mg/l/4h
ATE CA (oral)	7340 mg/kg bodyweight
Diiron trioxide (1309-37-1)	
LD50 oral rat	> 10000 mg/kg
Magnesium oxide (MgO) (1309-48-4)	
LD50 oral rat	3870 mg/kg
ATE CA (oral)	3870 mg/kg bodyweight
Calcium sulfate (7778-18-9)	
LD50 oral rat	> 3000 mg/kg
LC50 inhalation rat	> 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

<b>Calcium oxide (1305-78-8)</b>	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	> 5000 mg/kg bodyweight Animal: rabbit, Guideline: other:US Federal Register 38: 187, Part 1500, Section 41, 1973.
LC50 inhalation rat	> 6.04 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: 12 – 13 at 25°C / 77 °F
Serious eye damage/irritation	: Causes serious eye damage. pH: 12 – 13 at 25°C / 77 °F
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: May cause cancer if inhaled. Risk of cancer depends on duration and level of exposure.

<b>Diiron trioxide (1309-37-1)</b>	
IARC group	3 - Not classifiable

<b>Calcium sulfate (7778-18-9)</b>	
NOAEL (chronic, oral, animal/male, 2 years)	256 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)
NOAEL (chronic, oral, animal/female, 2 years)	284 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)

<b>Quartz (14808-60-7)</b>	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause respiratory irritation.

<b>Cement, portland, chemicals (65997-15-1)</b>	
STOT-single exposure	May cause respiratory irritation.

<b>Calcium hydroxide (1305-62-0)</b>	
STOT-single exposure	May cause respiratory irritation.

<b>Calcium oxide (1305-78-8)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

<b>Diiron trioxide (1309-37-1)</b>	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.2102 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.03 mg/l air Animal: rat, Animal sex: male

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Calcium sulfate (7778-18-9)	
LOAEL (oral, rat, 90 days)	237 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	79 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Calcium oxide (1305-78-8)	
LOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.413 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)

Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified.

Colored Mortar Mix	
Viscosity, kinematic	Not applicable

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.  
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.  
Symptoms/effects after eye contact : Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.  
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.  
Chronic symptoms : May cause cancer. Causes damage to organs through prolonged or repeated exposure.  
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : No known significant effects or critical hazards.

Diiron trioxide (1309-37-1)	
LC50 - Fish [1]	100000 mg/l (Exposure time: 96 h - Species: Danio rerio [static])
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):

Calcium sulfate (7778-18-9)	
LC50 - Fish [1]	2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 - Fish [2]	> 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Calcium oxide (1305-78-8)	
LC50 - Fish [1]	1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])
EC50 - Crustacea [1]	49.1 mg/l Test organisms (species): Daphnia magna
NOEC (chronic)	32 mg/l Test organisms (species): Crangon septemspinosa Duration: '14 d'
NOEC chronic fish	100 mg/l Test organisms (species): other:Tilapia nilotica Duration: '46 d'

### 12.2. Persistence and degradability

Colored Mortar Mix	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

Colored Mortar Mix	
Partition coefficient n-octanol/water	Not applicable
Bioaccumulative potential	Not established.

Calcium hydroxide (1305-62-0)	
BCF - Fish [1]	(no bioaccumulation)

Calcium oxide (1305-78-8)	
BCF - Fish [1]	(no bioaccumulation)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Other information : No other effects known.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

DOT NA No : Not applicable  
UN-No. (TDG) : Not applicable  
UN-No. (IMDG) : Not applicable  
UN-No. (IATA) : 1910

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Proper Shipping Name (IATA) : Calcium oxide

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : Not applicable

#### TDG

Transport hazard class(es) (TDG) : Not applicable

#### IMDG

Transport hazard class(es) (IMDG) : Not applicable

#### IATA

Transport hazard class(es) (IATA) : 8

Danger labels (IATA) : 8



### 14.4. Packing group

Packing group (DOT) : Not applicable

Packing group (TDG) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : III

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

#### DOT

No data available

#### TDG

No data available

#### IMDG

No data available

#### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.



# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

**⚠ WARNING:** This product can expose you to Silica, respirable crystalline, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	State or local regulations
Cement, portland, chemicals(65997-15-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Calcium hydroxide(1305-62-0)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Diiron trioxide(1309-37-1)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Magnesium oxide (MgO)(1309-48-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Calcium sulfate(7778-18-9)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Gypsum (Ca(SO4).2H2O)(13397-24-5)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Calcium oxide(1305-78-8)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Quartz(14808-60-7)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List

## SECTION 16: Other information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

Revision date : 10/18/2022  
Other information : None.  
Prepared by : Nexreg Compliance Inc.  
[www.Nexreg.com](http://www.Nexreg.com)



Full text of H-statements	
Carc. 1A	Carcinogenicity, Category 1A
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

SDS HazCom 2012 - WHMIS 2015 (Nexreg) - Section 15 2021

# Colored Mortar Mix

## Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012 and the Hazardous Products Regulations (HPR) WHMIS 2015

---

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.